2016

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 117

City of Lexington

Information in this report is included in Report

81

(Rockbridge County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	

(F241)	Frontage Road (F precedes frontage route number)

(600) Secondary Route

Virginia State Route

Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

							Tru	ıck			K	01/	Dir		
Route	Jurisdiction	Length AAD	T QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	Q
~ Clastinhum	From:	SCL Lex		070/	00/	10/	10/	10/	00/	_	0.004		0.510	10000	
S Lee Highway	City of Lexington	0.59 1100		97%	0%	1%	1%	1%	0%	С	0.094		0.512	12000	
1 N Lee Highway	City of Lexington	0.04 110 0		97%	0%	1%	1%	1%	0%	F	0.091		0.501	12000	
N Lee Highway	only of Lexington			31 /6	0 /6	1 /0	1 /0	1 /0	0 /6	•	0.031		0.501	12000	
1 N Lee Highway	City of Lexington	0.08 230 0		98%	0%	1%	0%	1%	0%	F	0.085		0.594	24000	
J) 11 200 1 11g1 1114)	To:	NCL Lex		0070	0 70		0,70	. , 0	0,0	•	0.000		0.00		
S	From:	SCL Lex	ington												
Main St	City of Lexington	0.39 260	0 F	98%	0%	1%	0%	0%	0%	С	0.106		0.515	2800	
<u> </u>	To: From:	Thornhi	ll Rd												
s Main St	City of Lexington	0.16 440	0 F	98%	0%	1%	0%	0%	0%	F	0.093		0.713	4700	
	To	Wallac	e St			— —									
ıs 1 Main St	City of Lexington	0.31 410		98%	0%	1%	0%	0%	0%	F	0.093		0.605	4400	
<u> </u>	To To	White		0070	0,0		0,70	0,0	0,0	•	0.000		0.000		
IS	From:			000/	00/	40/	00/	00/	00/	_	0.404			2222	
Main St	City of Lexington	0.31 270		99%	0% 1%	1%	0%	0%	0% 0%	F	0.121	F	0.603	2900	
	Combined Traffic Estimates for 2 Parallel Roadway			98%	170	1%	0%	0%	0%	Г	0.09	Г	0.603	4800	
ıs	From:	Nelson													
Main St	City of Lexington	0.24 470		99%	0%	1%	0%	0%	0%	F	0.089	_		5000	
	Combined Traffic Estimates for 2 Parallel Roadway			98%	1%	1%	0%	0%	0%	F	0.087	F	0.619	8300	
S	To: From:	Jefferso	on St												
Main St	City of Lexington	0.37 100 0	00 G	99%	0%	1%	0%	0%	0%	F	0.090		0.512	11000	
s	To: From:	Letche	r St												
Main St	City of Lexington	0.34 870	0 F	99%	0%	1%	0%	0%	0%	С	0.094		0.576	9200	
	То	US 11 N Lee Highwa	ıy; S Lee Hiş	ghway											
s	From:	Bus US 11		070/	40/	20/	00/	00/	00/	_	0.440			1000	
Jefferson St	City of Lexington Combined Traffic Estimates for 2 Parallel Roadway	0.35 180		97% 98%	1% 1%	2% 1%	0% 0%	0% 0%	0% 0%	F	0.118 0.09	F	0.603	1900 4800	
	Combined Traffic Estimates for 2 Parallel Hoadway			90%	1 70	1 76	0%	0%	0%	г	0.09	Г	0.003	4000	
s	From:	US 60 Ne													
Jefferson St	City of Lexington	0.24 310		97%	1%	2%	0%	0%	0%	С	0.105	_		3300	
	Combined Traffic Estimates for 2 Parallel Roadway	s on this Route: 780 Bus US 11		98%	1%	1%	0%	0%	0%	F	0.087	F	0.619	8300	
	From:	WCL Lex													
Nelson St	City of Lexington	0.25 380		98%	0%	1%	1%	0%	0%	С	0.096		0.724	4100	
ン	то то	Border													
Nelson St	City of Lexington	0.33 570		98%	0%	1%	1%	0%	0%	F	0.089		0.6	6000	
<u>ي</u>	To:	Glasgow	Street												

Virginia Department of Transportation Traffic Engineering Division 2016

Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		Tru			QC	K	QK	Dir	AAWDT	QW
							2AXIE	3+Axle	1 i raii	21raii		Factor		Factor		
	From:	G	lasgow Stre	et												
(60) Nelson St	City of Lexington	0.20	6000	F	98%	0%	1%	1%	0%	0%	F	0.085		0.532	6400	F
	To: From:	C2US	1-P, S Jeffe	erson St			_									
60 Nelson St	City of Lexington	0.11	7400	F	97%	1%	1%	0%	1%	0%	F	0.084		0.557	7900	F
\bigcirc	To:	,	Randolph S	t												
	From:	Ra	ındolph Str	eet												
(60) Nelson St	City of Lexington	0.21	7000	F	97%	1%	1%	0%	1%	0%	F	0.087		0.527	7400	F
	To: From:	S	potswood I)r			_									
(60) Nelson St	City of Lexington	0.35	13000	F	97%	1%	1%	0%	1%	0%	С	0.087		0.566	14000	F
	To:	ECL L	exington at	US 11												
	From:	W	CL Lexingt	on												-
(251) Thornhill Rd	City of Lexington	0.38	5000	F	97%	0%	1%	0%	2%	0%	С	0.092		0.629	5300	F
	To:		Link Rd													
	From:	,	Thornhill Ro	1												
251 Link Rd	City of Lexington	0.24	4600	F	97%	0%	1%	0%	2%	0%	F	0.091		0.722	4900	F
\smile	To:		Main St													

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

						City of Lexing	ton							
Route	Length	AADT	QA	4Tire	Bus	2Axle 3+Axle			QC	K Factor	QK Dir Factor	AAWDT	QW	Year
City of Lexington		From				Lewis St								
1 Diamond St	0.36	1200	F	97%	1%	1% 1%	1%	0%	С	0.207	0.642	1300	F	2016
·)		To				Main St								
		From				Nelson St								
2 Lee Ave	0.08	1500	F	97%	1%	1% 1%	0%	0%	С	0.101	0.553	1600	F	2016
		To				Washington S	St							
		From				Link Rd								
4251) Thornhill Rd	0.38	2000	F	99%	0%	0% 0%	0%	0%	С	0.109	0.817	2100	F	2016
		To				Main St								
		From				WCL Lexingto	on							
4252) Enfield Rd	0.43	1400	F	98%	0%	1% 0%	0%	0%	F	0.112	0.626	1500	F	2016
		To				Lime Kiln Ro	1							
		From				Enfield Rd								
4252 Lime Kiln Rd	0.32	2000	F	98%	0%	1% 0%	0%	0%	С	0.112	0.628	2200	F	2016
<u> </u>		To				McLaughlin S	St							
_		From				WCL Lexingto	on							
4254) Ross Rd	0.31	1000	F	98%	0%	1% 0%	0%	0%	F	0.102	0.64	1100	F	2016
$\overline{}$		To				Jackson Ave	:					17 2100 26 1500 28 2200 34 1100 28 2200 78 2000 78 2000 25 310 19 2800 83 1700 02 990 32 3600		
\bigcirc	-	From	<u> </u>	0651	0-1	Ross Rd		0.51				4=	_	001
Jackson Ave	0.27	1400	F	98%	0%	1% 0%	0%	0%	С	0.102	0.704	1500	F	2016
<u> </u>		То	<u> </u>			White St						3 1600 7 2100 6 1500 8 2200 4 1100 4 1500 8 2200 8 2000 5 310 9 2800 3 1700 2 990 2 3600		
_		From				SCL Lexingto	n							
Houston St	0.40	2100	F	98%	0%	1% 0%	0%	0%	С	0.101	0.528	2200	F	2016
		To				Taylor St								
Houston St	0.15	1900 From	F	98%	0%	1% 0%	0%	0%	F	0.1	0.578	7 2100 3 1500 3 2200 1100 4 1500 3 2200 3 310 9 2800 3 1700 2 990	F	2016
1200	0.10	To	Ė	0070	0 70	Main St	0 70	070	•	~~``	0.070	2000	•	2010
		From												
4256) McDowell St	0.05	290	F	99%	0%	Main St 1% 0%	0%	0%	С	0.117	0.625	210	_	2016
McDowell St	0.03	290 To		99 /0	0 /6	Jefferson St		0 /6	U	0.117	0.023	310	'	2010
O W II O	0.40	From	<u> </u>	000/	00/	Houston St	00/	00/	_		0.540	0000	_	0010
4257) Walker St	0.40	2600	F	99%	0%	1% 0%	0%	0%	С	0.097	0.519	2800	F	2016
<u> </u>		To				Nelson St								
		From				Main St								
4258) Preston St	0.05	1600	F	99%	0%	1% 0%	0%	0%	F	0.112	0.883	1700	F	2016
\bigcirc		To				Jefferson St								
		From				Main St								
4260) Henry St	0.05	930	F	99%	0%	1% 1%	0%	0%	С	0.098	0.702	990	F	2016
		To				Jefferson St						2 1300 3 1600 7 2100 6 1500 8 2200 4 1100 8 2200 8 2000 5 310 9 2800 9 2800 2 3600 0 3000 0 3000 8 3200 4 2900		
		From				Nelson St								
4261) Lewis St	0.08	3400	F	98%	0%	1% 1%	0%	0%	С	0.128	0.632	3600	F	2016
Lewis St	0.00	To	r.	5570	3 /0	Washington S		5,0		<u> </u>	3.002	5500	F F F F F F	_510
		From				Lewis St								
4261) Washington St	0.30	2800	F	98%	0%	1% 1%	0%	0%	F	0.104	0.710	3000	F	2016
(4261) Washington St	0.06	3000 From	F	98%	0%	Main St 1% 1%	0%	0%	F	0.093	0.648	3300	F	2016
Washington St	0.06	3000		30%	U 70			U 7/0	Г	0.093	0.048	3200	ı	2010
		To From				Jefferson St				\Box				
4261) Washington St	0.06	3900	F	98%	0%	1% 1%	0%	0%	F	0.092	0.633	4200	F	2016
$\overline{}$		To				Lee Ave				<u> </u>				
4261) Washington St	0.21	2700 From	F	98%	0%	1% 1%	0%	0%	F	0.092	0.664	2900	F	2016
3.2.0	*	To				Nelson St			-					
		From	 I											
4262) Borden Rd	0.34		F	98%	0%	WCL Lexingto	0%	0%	С	0.098	0.681	1200	_	2016
Borden Rd	0.34	1100 To		JO %	U 7/o		0%	U-/o	U	0.098	0.001	1200	Г	2016
		10	<u> </u>			Nelson St								
<u> </u>		From	<u> </u>			Washington S		.=		<u> </u>			_	
4263) Lewis St	0.33	1700	F	98%	0%	1% 1%	0%	0%	С	0.194	0.571	1800	F	2016
$\overline{}$		To				Diamond St							F F F F F F F F F F F F F F F F F F F	

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route City of Lexington

Length	AADT	QA	4Tire	Bus			• • • • • • • • • • • • • • • • • • • •		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
	P				**										
		_	2221							_				_	
0.40	2400	r	98%	0%			0%	0%	C	0.111		0.504	2600	F	2016
	To				No	lson St									
	From:				Jef	erson St									
0.18	1300	F	98%	0%	1%	0%	0%	0%	F	0.110		0.622	1400	F	2016
	To:				Mcl	aughlin St									
	From:				W	hite St									
0.28	2000	F	99%	0%	1%	0%	0%	0%	С	0.108		0.651	2100	F	2016
	To:				Gla	sgow St									
	From:				McL	aughlin St							•		
0.06	900	F	98%	0%	1%	0%	0%	0%	С	0.115		0.696	960	F	201
	To:				No	elson St									
	From:				McCo	orkle Drive									
	1400	G	98%	0%				0%	С	0.126		0.507	1400	G	201
	To:		0070	0 70			0 70	0 70				0.007	1400	ď	201
					Jacl	cson Ave								_	
		F								0.125		0.557	360	F	201
	To:				N	Iain St									
	From:														
					Wa	allace St									
	1400	F			Wa	allace St				0.132		0.585	1500	F	2016
	1400 _{To:}	F								0.132		0.585	1500	F	2016
	To	F			Но	ouston St				0.132		0.585	1500	F	201
	To:				Но										
	From:	F			Ho Was	ouston St hington St				0.132		0.585	1500 370	F	
	From: 70:				Ho Was	ouston St									2010
	70: From: 350 To:	F			Ho Was M US 1	hington St assie St 1 Main St				0.118		0.528	370	F	2016
	From: 70:		93%	3%	Ho Was	hington St assie St	1%	0%	C						2010
	70: From: 350 To:	F	93%	3%	Mass M US 1 2%	hington St assie St 1 Main St	1%	0%	C	0.118		0.528	370	F	201
	70: From: 350 To:	F	93%	3%	Mas Mus 1 2%	hington St assie St 1 Main St 1% allace St	1%	0%	C	0.118		0.528	370	F	2016
	70: 350 To: Prom: 1500 To:	F	93%	3%	Mas Mus 1 2%	hington St assie St 1 Main St 1%	1%	0%	C	0.118		0.528	370	F	
	0.40	0.18 1300 To From: 0.28 2000 To From: 0.06 900 To From: 1400 To	0.40 2400 F Tro From:	0.40	0.40	Length AADT QA 4Tire Bus 2Axle	Company	Company	Content of the cont	Column	Company	Company	Length AADT QA 4Tire Bus 2Axle 3+Axle 1Trail 2Trail QC Factor GK Factor	Company Comp	Company Comp