2016

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 140

Town of Abingdon

Information in this report is included in Report

95

(Washington County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	


(F241)	Frontage Road (F precedes frontage route number)


(600) Secondary Route

Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

Virginia State Route





Virginia Department of Transportation Traffic Engineering Division 2016

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Abingdon

			n of Abingo					Tru	ıck			K	Dir		
Route	Jurisdiction	Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK Factor	AAWDT	T QW
	From:	W	CL Abingdon	1											
11) (19) Main St	Town of Abingo	don 0.55	7800	F	95%	0%	1%	1%	3%	0%	F	0.091	0.59	8100	F
~ ~	To- From:	SR 1	40 Jonesboro	Rd											
11 (19) Main St	Town of Abingo	don 0.43	23000	F	98%	0%	1%	0%	1%	0%	F	0.088	0.541	25000	F
~ ~	To: From:		Colonial Rd												
11) (19) Main St	Town of Abingo	don 0.47	23000	F	98%	0%	1%	0%	1%	0%	F	0.088	0.532	24000	F
~ ~	To From:	US 19	Porterfield F	Iwy											
11 Main St/Lee Hwy	Town of Abingo	don 0.47	13000	F	98%	0%	1%	0%	1%	0%	F	0.089	0.502	14000	F
<u> </u>	To:		Palmer St				<u> </u>								
11 Main St	Town of Abingo	don 0.35	13000	F	98%	0%	1%	0%	1%	0%	С	0.087	0.501	14000	F
	To:		LT 58, Russel												
ALT 11 58 Main St	Town of Abingo		LT 58, Russel	F F	98%	0%	1%	0%	1%	0%	F	0.088	0.505	12000	F
(11) (38) Main St						0 70		070	1 /0	070	•	0.000	0.000	12000	•
11 Main St/Lee Hwy	Town of Abingo		, SR 75, Cum 11000	mings F	St 98%	1%	1%	0%	0%	0%	F	0.088	0.505	12000	F
11 Main St/Lee Hwy	Town of Abingo	0.00		'	30 76	1 /0	1 70	0 70	0 70	0 70	'	0.000	0.505	12000	
Main Ct/Lea Llun	Town of Abines	don 0.00	Tanner St	_	000/	1%	10/	00/	00/	00/	F	0.005	0.507	14000	F
11 Main St/Lee Hwy	Town of Abingo	don 0.93	13000	F	98%	1%	1%	0%	0%	0%	Г	0.085	0.507	14000	Г
~~~\undersity \( \text{1.1} \\ \text{2.11} \\ \text{1.1} \\ \text{2.11} \\	To- From:		Thompson Dr		000/	10/		00/	00/	00/		0.000	0.500	00000	
11 Main St/Lee Hwy	Town of Abingo	don 0.13	19000	F	98%	1%	1%	0%	0%	0%	F	0.090	0.523	20000	F
~~~	To- From:		Hillman Hwy		2221									.=	
Main St/Lee Hwy	Town of Abingo		16000	F	98%	1%	1%	0%	0%	0%	С	0.089	0.532	17000	F
•	From:		CL Abingdon												
19 (11) Main St	Town of Abingo		CL Abingdon 7800	F	95%	0%	1%	1%	3%	0%	F	0.091	0.59	8100	F
19) (11) Main St	Town of Abingo				33 76	0 70	1 /0	1 /0	J /0	0 70	'	0.031	0.55	0100	
19 (11) Main St	Town of Abingo		40 Jonesboro 23000	Rd F	98%	0%	1%	0%	1%	0%	F	0.088	0.541	25000	F
19 (11) Main St	Town of Abingo				90 /6	0 /6	1 /0	0 /6	1 /0	0 /6	'	0.000	0.541	23000	'
Main Ct	Tour of Abines		Colonial Rd 23000	_	000/	00/	10/	00/	10/	00/	F	0.000	0.500	04000	
19 11 Main St	Town of Abingo		S 11 Main St	F	98%	0%	1%	0%	1%	0%	Г	0.088	0.532	24000	F
	From:		Main St; Lee												
19 Porterfield Hwy	Town of Abingo	don 0.45	17000	F	95%	0%	1%	1%	3%	0%	F	0.089	0.540	18000	F
<u> </u>	To		Alt US 58												
ALT 19 58 Porterfield Rd	Town of Abingo	don 0.21	22000	F	95%	0%	1%	1%	3%	0%	_	0.089	0.566	24000	F
19 58 Porterfield Rd	Town of Abingo		CL Abingdon		95%	076	170	1 70	3%	0%	Г	0.069	0.566	24000	Г
	From:														
58 (81)	Town of Abingdon (M		CL Abingdon		Si	ee I-81	for direc	ctional tr	affic vo	lume es	timate	es for this	segment.		
(30) (01)	Combined Traffic Estimates for 2 Parallel R		45000	F	80%	1%	1%	1%	17%	1%		0.096	A 0.511	46000	F
	To:	ioadirayo on ino riodio.	SR 75	•	50 /0	1 /0		1 /0	17.70	1 /0	0	3.000	7. 0.011	40000	

4/27/2017 7

Virginia Department of Transportation Traffic Engineering Division 2016

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Abingdon

	1				47.			Trι	ıck			K	014	Dir	A A14/DT	0111
Route	Jurisdictio	n Length	AADT	QA	4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	QW
~ ~	From:	(14.1	SR 75						***							
[58] [81]	Town of Abingdon (_								es for this				_
	Combined Traffic Estimates for 2 Parallel		CL Abingdo	F	80%	1%	1%	1%	17%	1%	F	0.079	F	0.501	48000	F
A. T	Franci						_									
ALT (58) (19) Porterfield Rd	Town of Abing		CL Abingde 22000	on F	95%	0%	1%	1%	3%	0%	F	0.089		0.566	24000	F
(58) (19) 1 orternola ria						0 70		1 /0	0 70	070	•	0.000		0.000	24000	•
ALT	From:		9 Porterfield													
(58) Russell Rd	Town of Abin		8800	F	99%	0%	0%	0%	0%	0%	С	0.092		0.525	9400	F
ALT	To: From:	`	Valley Stree Valley St	t												
58 11 Main St	Town of Abing	gdon 0.24	11000	F	98%	0%	1%	0%	1%	0%	F	0.088		0.505	12000	F
	To:		Main St													
ALT	From:		US 11		000/	00/	101	00/	40/	00/	_			0.540	10000	_
58 75 Cummings St	Town of Abing	gdon 0.78	17000	F	99%	0%	1%	0%	1%	0%	С	0.086		0.549	18000	F
			I-81													
75 Green Spring Rd	Town of Abing		ingdon Cour 8000	ntry Club F	97%	0%	1%	1%	1%	0%	С	0.087		0.627	8600	F
75 Green Spring Rd	To:		Commerce		31 /6	0 70	1 /0	1 /0	1 /0	0 70	O	0.007		0.027	0000	
ALT	From:		I-81													
75) (58) Cummings St	Town of Abing		17000	F	99%	0%	1%	0%	1%	0%	С	0.086		0.549	18000	F
<u> </u>	Τα	U	S 11 Lee Hy	wy												
North	From:		CL Abingdo	on _							_					_
81) [58]	Town of Abingdon (,	23000	F	78%	1%	1%	1%	19%	1%	С	0.094			23000	F
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	45000	F	80%	1%	1%	1%	17%	1%	С	0.096	Α	0.511	46000	F
North	To: From:	SR '	75 Cumming	gs St												
(81) (58)	Town of Abingdon ((Maint: 95) 1.06	23000	F	78%	1%	1%	1%	19%	1%	F	0.079			24000	F
$\circ \circ$	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	47000	F	80%	1%	1%	1%	17%	1%	F	0.079	F	0.501	48000	F
	To:	N	CL Abingdo	on												
South	From:		CL Abingdo													
81) (58)	Town of Abingdon ('	22000	Α	81%	1%	1%	1%	15%	1%	С	0.103			23000	Α
\checkmark \checkmark	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	45000	F	80%	1%	1%	1%	17%	1%	С	0.087	В	0.530	46000	F
South	To: From:	SR ′	75 Cumming	gs St												
81) (58)	Town of Abingdon ((Maint: 95) 0.79	23000	F	81%	1%	1%	1%	15%	1%	F	0.08			24000	F
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	47000	F	80%	1%	1%	1%	17%	1%	F	0.079	F	0.501	48000	F
	To:	N	CL Abingdo	on												
	From		CL Abingdo	on												
140 Jonesboro Rd	Town of Abing	•	17000	F	94%	1%	1%	1%	4%	0%	С	0.091		0.544	19000	F
\smile	To	U	S 11 Main	St												

4/27/2017

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Abingdon

						TOWN	ot Abingd	on								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle		2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
own of Abingdon																
1 VHCC Dr	0.63	2100				SR 140	Jonesboro l	Rd			0.139		0.576	2100	F	2016
1 VHCC Dr	0.03	2100 To			I	Faculty Pa	arking; VHC	'C Dr			0.139		0.576	2100	Г	2010
		From	1				1 VHCC Dr				1					
2 Partnership Circle	0.10	1600	F			140-	I VIICE DI				0.147		0.578	1600	F	2016
2 Partnership Circle	0.10	То	Ė			VHC Col	lege Parking	2 Lot			1 7		0.070	1000	•	2010
		From					L Abingdon	,			l					
3 Wyndale Rd	1.07	3800	F	98%	1%	0%	0%	0%	0%	С	0.105		0.563	4000	F	2016
<u> </u>		То					11 Main St									
		From				US	11 Main St									
Thompson Dr	0.19	4800	F				11 Man ot				0.168		0.671	4800	F	2016
		To				S	tanley St									
		From				140-30	003 Valley S	St								
6 Court St	0.08	1200	F			0					0.124		0.785	1300	F	2016
•		To				US	11 Main St									
		From			U	JS 11 Lee	Hwy; W M	ain St								
3002) Cummings St	0.08	7100	F	99%	0%	0%	0%	0%	0%	F	0.091		0.561	7600	F	2016
		To				7	/alley St									
		From				Russel	l Rd; ALT 5	58								
Valley St	0.72	9200	F	99%	0%	0%	0%	0%	0%	С	0.1		0.536	9800	F	2016
,		To					Court St				_					
3003) Valley St	0.14	6500 From	F	99%	0%	0%	0%	0%	0%	F	0.108		0.506	6900	F	2016
Valley St	0.14	То	Ė	00 /0	0 70		tes Mill Rd	0 70	0 70	•	0.100		0.000	0000	'	2010
		From					11 Main St									
Tanner St	0.08	1500	F	98%	1%	1%	0%	0%	0%	F	0.089		0.584	1600	F	2016
3004) Tarmer St	0.00			0070	1 /0			0 70	0 70		0.000		0.004	1000	'	2010
Militara Mill Dal	0.07	From	<u> </u>	000/	10/		/alley St	00/	00/		0.001		0.007	0000		0010
Whites Mill Rd	0.87	2100 _{To}	F	98%	1%	1%	0%	0%	0%	С	0.091		0.627	2200	F	2016
							ICL Abingdo)II								
Hillman Hun	1 25	From	ᆫ	99%	0%	1%	1; Lee Hwy 0%	0%	0%		0.097		0.562	4600	_	2016
Hillman Hwy	1.35	4400 To	F	99%	076		Abingdon	076	0%	С	0.097		0.362	4600	F	2016
			<u> </u>													
Tunnel St/Old Saltw	orke EMO	From	F	98%	1%	140-300 1%	5 Hillman H 0%	1wy 0%	0%	F	0.092		0.677	1600	F	2016
1 unnei St/Old Saitw	OIV2 MUUO	1500 _{To}		JU 70			140 NCL Ab		U 70	Г	0.092		0.077	1000	1,	2010
		From			73			mguUII								
Augusta Dr		410	F			Saw	grass Circle				0.095		0.614	430	F	2016
Augusia DI		410 To				W/:-	nterham Dr				0.095		0.014	430	ı	2010
		From														
Bradley St		1300	F			P	reston St				0.102		0.569	1300	F	2016
Diauley St		1300 To				ī	Fuller St				0.102		0.568	1300	1,	2010
		From														
Fairway Dr			ᆫ			В	Bogey Dr				0.127		0.764	440	F	2016
i aliway Di		410 To	F			ר	ead End				0.127		0.764	440	1,	2010
		From														
Oak Hill St		240	F			H	illside Dr				0.13		0.576	260	F	2016
Oak Mill St		240 To				Ctor-	woll Haiate	0			0.13		0.576	∠00	۲	2016
						Stone	wall Height	8								

4/27/2017 9