2016

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 148

Town of Richlands

Information in this report is included in Report

92

(Tazewell County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	

(F241)	Frontage Road (F precedes frontage route number)

(600) Secondary Route

Virginia State Route

Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Richlands

			n of Richia					Tru	ıck			K		Dir		
Route	Jurisdictio	on Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	QW
	From:		WCL Richland													
67	Town of Richl		5000	N	91%	1%	0%	3%	5%	0%	N	0.088		0.547	5300	N
	To: From:		US 460 From JS 460 Raver													
(67) (460)	Town of Richlands		13000	G	96%	0%	1%	1%	2%	0%	F	0.083		0.503	15000	G
(i) (400)	To:	,	CL Richlands	3												
Bus	From:		460; BUS US								_					_
67 460 Front St	Town of Richl	lands 0.27	13000	G	98%	0%	0%	1%	1%	0%	С	0.082		0.518	14000	G
Bus	To:	BUS	US 460 P, 21	nd St												
67) (460) Front St	Town of Richl	lands 0.58	6400	G	98%	0%	0%	1%	1%	0%	F	0.082		0.539	6800	G
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	13000	G	98%	0%	1%	1%	1%	0%	F	0.084	F	0.786	14000	G
	To	SR 6	7 P Railroad	Ave												
8us Bus Front St	Town of Richl		5700	G	99%	0%	1%	0%	0%	0%	F	0.089			6100	G
67 460 460 Front St	Combined Traffic Estimates for 2 Parallel			N	98%	0%	1%	1%	0%	0%	N	NA			10000	N
	Combined Traine Estimates for 2 Taraner	<u>-</u>			0070	0 70		170	0 70	070		1471			10000	.,
67 Norfolk St	From: Town of Richl		US 460 From 1100	nt St G	96%	0%	1%	3%	1%	0%	F	0.095		0.696	1200	G
67 Noriok St	Combined Traffic Estimates for 2 Parallel			G	95%	0%	1%	3%	1%	0%	F	0.103	F	0.842	2000	G
	To:	Tioadways off this floute.	2nd St	<u> </u>	33 /6	0 70	1/0	378	1 /0	0 70	'	0.100	•	0.042	2000	ч
Bus	From:		Norfolk St													
67) (460) 2nd St	Town of Richl		4000	N	96%	0%	1%	3%	1%	0%	N	0.095		0.664	4300	N
~	Combined Traffic Estimates for 2 Parallel			N	98%	0%	1%	1%	0%	0%	N	NA			10000	N
	From:	SR 67 Par, B	us US 460 Pa Bus US 460													
67) Railroad St	Town of Richl	·	4000	G	96%	0%	1%	3%	1%	0%	F	0.095		0.664	4300	G
	To		US 460													
67 Railroad St	Town of Richl	lands 0.92	2300	G	95%	0%	1%	3%	1%	0%	С	0.091		0.519	2400	G
	To:	N	ICL Richland	ls												
	From:	Bus	US 460 Fron	nt St												
Railroad St	Town of Richl	lands 0.05	810	G	95%	0%	1%	3%	1%	0%	F	0.115			860	G
P	Combined Traffic Estimates for 2 Parallel			G	95%	0%	1%	3%	1%	0%	F	0.103	F	0.842	2000	G
	То	Si	R 67 Second	St												
~~~	From:		VCL Richland													
460	Town of Richlands	(Maint: 92) 0.23	7700	N	96%	0%	1%	1%	2%	0%	N	0.085		0.59	8500	N
<del>~</del>	To: From:		SR 67													
(460) (67)	Town of Richlands	(Maint: 92) 1.38	13000	G	96%	0%	1%	1%	2%	0%	F	0.083		0.503	15000	G
~~~	<u>To:</u> From:		Bus US 460													
460	Town of Richlands	(Maint: 92) 1.32	10000	G	96%	0%	1%	1%	2%	0%	F	0.082		0.558	11000	G
<u> </u>	To: From		SR 67													
460	Town of Richlands		13000	Α	96%	0%	1%	1%	2%	0%	С	0.102		0.507	14000	Α
<u> </u>	To	F	ECL Richland	s		-										

Virginia Department of Transportation Traffic Engineering Division 2016

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Richlands

Doute	Jurisdiction	Longth	AADT	0.4	4Tire	Due		Tru	ıck		QC	K	QK	Dir	AAWDT	OW
Route	Junsaiction	Length	AADT	QA	41lle	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QN	Factor	AAWDI	QW
Bus	From:		US 460		2221											_
(460) (67) Front St	Town of Richlands	0.27	13000	G	98%	0%	0%	1%	1%	0%	С	0.082		0.518	14000	G
Bus	To: From:	Bus U	JS 460 P, 2	nd St												
460 67 Front St	Town of Richlands	0.58	6400	G	98%	0%	0%	1%	1%	0%	F	0.082		0.539	6800	G
\bigcirc	Combined Traffic Estimates for 2 Parallel Roadways on t	his Route:	13000	G	98%	0%	1%	1%	1%	0%	F	0.084	F	0.786	14000	G
Bus	Toe From:	SR 6	7 P Railroac	l Ave			\Box \vdash									
460 67 Front St	Town of Richlands	0.04	5700	G	99%	0%	1%	0%	0%	0%	F	0.089			6100	G
(400) (07)	Combined Traffic Estimates for 2 Parallel Roadways on t	his Route:	9700	N	98%	0%	1%	1%	0%	0%	Ν	NA			10000	N
	то	SR	67 Norfolk	St												
Bus Front St	Town of Richlands	0.18	3800	G	99%	0%	1%	0%	0%	0%	_	0.088			4000	G
Front St	Combined Traffic Estimates for 2 Parallel Roadways on t		6900	G	99%	0%	1%	0%	0%	0%	F	0.000	F	0.549	7400	G
	Tanic Estimates for 21 araner roadways on t				33 /6	0 76	1 /0	0 /6	0 /6	0 /6	'	0.030	'	0.543	7400	ч
Bus	From:		US 460 P 21	nd St												
(460) Front St	Town of Richlands	0.92	6500	G	99%	0%	1%	0%	0%	0%	С	0.096		0.54	6900	G
<u>~</u>	Τα		CL Cedar B													
Bus and St	Town of Richlands		US 460 Fro		99%	0%	1%	00/	0%	00/	_	0.007			7500	_
460 (67) 2nd St	Combined Traffic Estimates for 2 Parallel Roadways on t	0.57	7000 13000	G G	99% 98%	0% 0%	1%	0% 1%	0% 1%	0% 0%		0.087 0.084	F	0.786	7500 14000	G G
	Combined Tranic Estimates for 2 Faraner hoadways of t				90%	0%	1 70	170	1 70	076	Г	0.064	Г	0.766	14000	G
Bus	To: From:	SR 6	7 Railroad	Ave												
(460) (67) (67) 2nd St	Town of Richlands	0.05	4000	N	96%	0%	1%	3%	1%	0%	Ν	0.095		0.664	4300	N
	Combined Traffic Estimates for 2 Parallel Roadways on t	his Route:	9700	N	98%	0%	1%	1%	0%	0%	Ν	NA			10000	N
Bus	Tec From:	SR	67 Norfolk	St												
(460)2nd St	Town of Richlands	0.25	3100	G	99%	0%	1%	0%	0%	0%	С	0.090			3300	G
ر به ع	Combined Traffic Estimates for 2 Parallel Roadways on t	his Route:	6900	G	99%	0%	1%	0%	0%	0%	F	0.090	F	0.55	7400	G
	To:	Bus	US 460 Fro	nt St												

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Richlands

						I own of Richlands							
Route	Length	AADT	QA	4Tire	Bus	Truck 2Axle 3+Axle 1Trail 2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Richlands		E				D 15 1							
Fec. Park Rd	0.72	740	G			Dead End		 0.132		0.513	740	G	2016
3)	•	Te				SCL Richlands							
		From				Dead End							
6 Purcell Rd	0.25	60	R					0.178		0.5	NA		01/06/2000
<u> </u>		T _c From				148-4 Birmingham Rd		_					
6 Purcell Rd	0.65	1100	R					0.107		0.615	NA		12/17/2002
		To	1			SCL Richlands							
Durnott Ct	0.40	From	<u> </u>			Dead End		0.001		0.6	NIA		10/17/000
7 Burnett St	0.40	1000 To	R			WCL Richlands		0.091		0.6	NA		12/17/200
		From				Cul-de-Sac							
8 Sandy Lane	0.19	140	R			Cui-ue-sac		 0.129		0.515	NA		1986
,		To				148-13 Cresswood Dr							
8 Cresswood Dr	0.07	510 From	R			146-13 Clesswood DI		0.095		0.643	NA		1986
		To				148-12 Valley Dr							
8 Cresswood Dr	0.21	490 From	R			146-12 Valley DI		0.09		0.740	NA		1986
0		To				148-11 Plantation Dr							
8 Cresswood Dr	0.16	870 From	R			146-11 Flantation Di		0.102		0.524	NA		1986
0		To				148-9 Fairmont Dr							
8 Cresswood Dr	0.16	880 From	R			146-9 Fairnioni Dr		0.097		0.671	NA		1986
		To				148-15 Terry Dr							
8 Cresswood Dr	0.27	2000 From	R			146-13 Teny Dr		0.096		0.524	NA		12/17/200
8 Gresswood Br		To				148-4700 Kents Ridge Rd							,,,
		From	1			148-10 Linwood Dr							
9 Fairmont Dr	0.07	290	R					0.122		0.623	NA		1986
\bigcirc		To	1			148-8 Cresswood Dr							
O		From	L			148-9 Fairmont Dr							
(10) Linwood Dr	0.20	280	R					0.147		0.629	NA		1986
<u> </u>		To From				148-11 Plantation Dr]					
(10) Linwood Dr	0.08	80 To	R			0.1.1.0		0.238		0.579	NA		1999
		From	<u> </u>			Cul-de-Sac							
11) Plantation Dr	0.07	470	R			148-15 Terry Dr		 0.131		0.531	NA		1986
(11) Flamation Br	0.07	-7.0	<u></u>			140.10.0		-		0.001	100		1000
11) Plantation Dr	0.27	100 From	R			148-13 Cresswood Dr		0.164		0.739	NA		1986
(11) Plantation Dr	0.27	100				140.00		JU		3., 00	. 47 1		. 500
11 Plantation Dr	0.06	140 From	R			148-8 Cresswood Dr		0.168		0.529	NA		1986
(11) Plantation Dr	0.00	To	<u> </u>			148-10 Linwood Dr		7		3.020	. 47 1		. 500
		From	4			148-14 Cresswood Dr							
(12) Valley Dr	0.16	250	R					0.142		0.871	NA		1986
\bigcup		To				148-8 Cresswood Dr							
		From				148-11 Plantation Dr							
(13) Cresswood Dr	0.15	240	R					0.128		0.702	NA		1986
<u> </u>		From				148-14 Valley Dr							
(13) Cresswood Dr	0.10	160	R					0.148		0.654	NA		1986
<u> </u>		To From				148-15 Hawthorn Ln							
(13) Cresswood Dr	0.13	300	R					0.146		0.625	NA		1986
		To	1		148	-8 Cresswood Dr; Sandy Lane							
Valley Dr	0.06	Prom 250	<u> </u>			148-13 Cresswood Dr				0 071	NIA		1006
14) Valley Dr	0.06	250	R			148-12 Valley Dr		0.142		0.871	NA		1986
						170-12 vancy DI							

Virginia Department of Transportation Traffic Engineering Division 2016 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Richlands

						TOWIT	oi Riciliai	ius									
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle	-		QC	K Factor	QK	Dir Factor	AAWDT	QW	Year	
Town of Richlands																	
15) Terry Dr	0.27	240	R			148-13	Hawthrone	La			0.163		0.758	NA		1986	
(15) Terry Dr	0.38	590 From	R			148-11	Plantation	Dr			0.130		0.672	NA		1986	
(15) Terry Dr	0.07	740 From	R				16 Gary Dr				0.123		0.663	NA		1986	
		To					Cresswood										
(16) Gary Dr	0.37	240	R				15 Terry Di	•			0.150		0.625	NA		1986	
		10					ead End										
0xford St	0.34	390	G]		; 613 Hayes				0.104		0.610	390	G	2016	
<u> </u>		To	<u> </u>				7 Burnett St										
18) Hunter Ridge Rd	0.51	90	R				ead End				0.129		0.512	NA		12/17/200	
<u> </u>		То			WC	L Richlar	nds; Kents I	Ridge Rd									
19) Daw Rd	0.73	350	G				L Richlands				0.104		0.68	350	G	2016	
		To					Kents Ridg	ge Rd								01/25/20	
20) Laramie Rd	0.22	820	R										0.512	NA		01/25/200	
<u> </u>		10					ead End										
O Diamain ahama Dal	1.00	From	ᄂ			148-4700	Kents Ridg	e Rd					0.011	NIA		04/00/000	
21 Birmingham Rd	1.20	290 To	R			1/18/	6 Purcell Ro	ı			0.138		0.611	NA	G	01/06/200	
		From															
4700 Kents Ridge Rd	0.46	3000	G	99%	0%	0%	SCL Richla	0%	0%	F	0.095		0.516	3200	G	2016	
(4700) Kents Ridge Rd	0.34	3200 From	G	99%	0%	148 0%	-2 Daw Rd 0%	0%	0%	F	0.092		0.543	3400	G	2016	
		To From				148-8	Cresswood	Dr									
4700) Kents Ridge Rd	0.62	4200	G	99%	0%	0%	0%	0%	0%	С	0.098		0.61	4400	G	2016	
<u> </u>		To From				В	urnett St										
4700 Kent Ridge Rd	0.29	5700	G	99%	0%	0%	0%	0%	0%	F	0.093		0.606	6100	G	2016	
<u> </u>		From					eteran St eteran Dr										
Kent Ridge Rd	0.47	4900 _{то}	G	99%	0%	0%	0% S 460 Front	0% St	0%	F	0.094		0.563	5200	G	2016	
		From					t Ridge Rd	IJί									
S Front St		390 _{то}	G				linch Rd				0.120		0.505	420	G	2016	
		From					t Ridge Rd										
Veteran Dr		2100 To	G				2nd St				0.106		0.608	2200	G	2016	
							-41G () (